

	PRODUCT	SCREW LEAD (mm/rev)	RATED FORCE (KN)	DYN. LOAD RATING (KN)	CATALOG LIFE @ CATALOG FORCE (mmx10^6)	CALCULATED LIFE @ I SERIES FORCE (mmx10^6)
IX20	IX20-xx01	2.54	2.571	10.987	198.2	198.2
	GSX20-xx01	2.54	2.571	9.230	NA	117.5
	KX60-05	5.00	2.571	12.200	41.7	534.2
	IX20-xx02	5.08	1.713	10.111	1,049.0	1,044.7
	GSX20-xx02	5.08	1.713	6.850	NA	324.8
	KX60-05	5.00	1.713	12.200	41.7	1,806.2
	IX20-xx04	10.16	0.854	6.036	3,571.2	3,587.3
GSX20-xx04	10.16	0.854	5.471	NA	2,671.3	
KX60-10	10.00	0.854	10.800	461.4	20,225.4	
IX30	IX30-xx01	2.54	5.992	22.793	139.8	139.8
	GSX30-xx01	2.54	5.992	24.536	NA	174.4
	KX75-05	5.00	5.992	25.600	60.7	389.9
	IX30-xx02	5.08	4.026	19.127	546.1	544.7
	GSX30-xx02	5.08	4.026	25.798	NA	1,336.6
	KX75-05	5.00	4.026	25.600	60.7	1,285.5
	IX30-xx05	12.70	1.610	20.680	26,918.2	26,914.0
GSX30-xx05	12.70	1.610	21.795	NA	31,506.2	
KX75-10	10.00	1.610	21.400	573.3	23,483.5	
IX40	IX40-xx01	2.54	17.642	37.757	25.4	24.9
	GSX40-xx01	2.54	17.642	35.141	NA	20.1
	KX90-05	5.00	17.642	51.400	179.6	123.7
	IX40-xx02	5.08	11.975	37.774	160.0	159.4
	GSX40-xx02	5.08	11.975	36.920	NA	148.9
	KX90-05	5.00	11.975	51.400	179.6	395.4
	IX40-xx05	12.70	4.791	27.712	2,461.2	2,457.7
GSX40-xx05	12.70	4.791	31.271	NA	3,531.4	
KX90-10	10.00	4.791	47.700	2,295.0	9,869.1	